

MODEL	NCTS-R3K96	
PICTURE		

Rack-Mounted UPS

Capacity :3000va / 2400w

- True double-conversion online UPS
- Micro processor control optimizes reliability
- Output power factor 0.8
- Wide Input voltage range(110V – 300VAC)
- Input power factor correction
- Converter mode available
- ECO mode for energy saving
- Generator compatible
- Smart SNMP works well with either USB or RS-232 together
- Comprehensive display allows easy monitoring and access of UPS status
- True Isolation technology offers the most complete power protection and highest quality power for all IT applications.
- SNMP Slots for remote monitoring and control
- Load sensing, overload protection, dynamic by-pass, temperature monitoring software for preventative diagnostics.
- LED / LCD option
- Extended backup time capacity
- Zero transfer time

Rated capacity	3KVA /2.4KW
Format	2U
Input Voltage Range	115-300 VAC ± 5
Input Frequency Range	(45 -55) ± 0.5Hz
Input Bypass Range	80VAC x (1 ± 5%) – 285VAC x (1 ±5%)
BATTERY Voltage	96VDC
BATTERY Capacity and Quantity	External battery
BATTERY charge current	4A
Output Voltage	220VAC ± 1% (invert output)
Output Frequency	46 - 54Hz (normal AC output); 50Hz ± 1% (abnormal AC output)
Output Wave Form	Sine wave THD < 3% (linear load); sine wave THD <8% (nonlinear load)
Overload	105 - 125%: convert to byass after 1 minute
Output Power Factor	0.8
Output Current Peak Factor	3 : 1
Communication & monitoring	RS232 / USB+software+cable , SNMP slot
N.G. (KG)	10.3
Unit size	440*590*89mm
Package Size (mm)	560*530*180
Application area	OFFICE, IT ROOM, INDUSTRIAL ENVIRONMENT, Security and Protection System, Communication System and Computer Network System
Certification	ISO9001, ISO14001, CE, ROHS