


NEW COMPUTER TECHNOLOGY SYSTEMS (NCTS) LIMITED COMPANY

新计算机科技系统 (NCTS) 有限公司

深圳市龙岗区布吉诚信华庭2栋6B

www.ncts.co

<p>NCTS-IN06A2 Cat6A Indoor Cable Specification Sheet 500m/roll</p>		 <p>NCTS-IN06A2</p> <p>CAT6A INDOOR CABLE CONDUCTOR:0.58mm Copper INSULATION DIA:0.98±0.02mm Unrip Rope:Nylon Yarn Shield :Al foil+Mylar Shielding Aluminum Foil Jacket:6.5mm±0.2MM NEW PVC</p> <p>Cat6A U/FTP Indoor</p>	
Brand:	NCTS	Color:	light GREY
Conductor Material:	Copper	Conductor Size:	23AWG (0.58mm)
Conductor :	Solid	Twisted Pair:	4PAIRS
Structure:	4P+F Twisted Pair	Jacket Material	PVC
Insulation Material:	PE	Insulation Diameter:	1.0mm(±0.02mm)

Insulation Thickness:	0.18mm	Jacket Thickness:	0.65mm(±0.02mm)
Outer diameter:	6.5mm(±0.2mm)	Stretching Resistance:	(max)450N
Impedance:	100±15%Ω	Frequency:	500MHz
Flame Retardancy Standard:	CM / CMR		
Reference standard:	YD/T1019-2001, ISO/IEC 11801, ANSI / TIA / EIA-568B, UL444		
Feature & Advantages:	CAT6A Cable is designed for improve crosstalk performance between cables applying in 1000Base-T Ethernet with up to 500MHz bandwidth.HDPE insulation and pair shield design make the cable with excellent shielding & anti-EMI performance.		
Application:	Mainly used in the wiring system between work area correspondence leading-out terminal and distribution wiring frames connection. As well as used in the housing synthesis wiring system between user correspondence leading out terminal and patch panel.		