NEW COMPUTER TECHNOLOGY SYSTEMS (NCTS) LIMITED COMPANY

新计算机科技系统 (NCTS) 有限公司

深圳市龙岗区布吉诚信华庭2栋6B

www.ncts.co

SPECIFICATIONS:

COAXIAL CABLE NCTS-KX7

NCTS-KX7 is apply for CATV-community antenna television, CCTV-closed-circuit television and DBS-direct broadcasting satellite. It has a characteristic impedance of 75 ohms, its Excellent transmission with fast speed.

Conductor	Bare Copper
Conductor Dia.	Stranded 7*0.2mm
Insulation	Solid PE
Insulation Dia.	3.7mm
Shield	Aluminium Foil
Braid Shielding	CCA/AL
Braid Coverage Area (%)	60%-100%
Jacket	PVC
Jacket Dia	6.0mm
Color	Green
Length&Package	100/200 with PE film Packing
	305m/500m with wooden reel packing
ELECTRICAL CHARACTERISTICS FOR Kx6/Kx7:	
Max.DC Inner Conductor Resistance	87.5 Ohm/km
Max.DC Outer Conductor Resistance	32.5 Ohm/km
Characteristic Impedance	52±2Ω
Nom. Mutual Capacitance	67 pf/m
Velocity Radio	66%
Dielectric Strength	1000 vac
Min. Insulation Resistance	5000 MOhms*km
Operating Voltage	300V
Coaxial cable signal (Attenuation)Loss per 100 ft	
Frequency(MHz)	Max.Attenuation(db/100ft)
5 MHZ	0.92db
55MHZ	2.21db
200 MHZ	4.09db
400MHZ	5.49db
550MHz	6.40db
750 MHZ	7.50db
870 MHZ	8.09.0db
1000MHz	8.73db