

# NCTS-NU17WP (15V OUTPUT & 24V)

## MINI UPS POE PORT 15V/24V SELECTABLE

## NCTS-NU17WP (15V OUTPUT & 24V)

GTIN 6295151550410

### Product Features

- Input Voltage: 100-240VAC
- Output DC 5V/9/12V
- Output POE 15V /24V Selectable
- 8800mah lithium battery
- Press 2-3 seconds to turn on UPS
- Suitable for small DC communication equipment, network peripherals

### Product Instructions

- The UPS automatically begin charging after the power is plugged in
- Manually control output switch
- Overload & short-circuit protection
- Over-charge and over-discharge protection
- Multi-functional LCD screen
- Maximum capacity: 60W
- Application:router, modem,wireless phone,CCTV.,etc.

### Warm prompt

For getting more fun and the best possible performance,please read carefully the user manual before you use this product.

Please charge the UPS once every 3 months if it is not used for a long time.

It is normal that the temperature is a bit high during charging.

Please keep the UPS clean and dry, do not wash it with chemistry depurative.

Please protect environment,do not abandon.



# NCTS-NU17WP (15V OUTPUT & 24V)

## MINI UPS POE PORT 15V/24V SELECTABLE

### Technical Specifications

Model: NCTS-NU17WP

GTIN 6295151550410

#### Model

#### NCTS-NU17WP

Input voltage	100-240Vac/50-60Hz			
Output Power	17W			
Output	USB/DC1	DC2	DC3	POE interface
Output voltage(Optional)	5Vdc	9Vdc	12Vdc	15V/24Vdc
Output polarity		— ⊖ ⊕		+4,5pins -7,8pins
Output voltage & current	5V/2.4A	9V/1.8A	12V/1.35A	15V/1A or 24V/0.63A
QTY.&capacity of battery	Lithium battery 2200mAhx4			
Unit dimension(mm)	160*105*27.3mm			
Net weight(kg)	0.38kg			
Charging time(h)	3h			
Operating temperature	0°C~40°C			
Storage temperature	-15°C~45°C			

\* Product specifications are subject to change without notice.

