

NCTS-NU60WP (9V OUTPUT & 12V) MINI UPS POE PORT 15V/24V SELECTABLE

NCTS-NU60WP (9V OUTPUT & 12V)

GTIN 6295151550441

Product Features

- Input Voltage: 100-240VAC
- Output POE 15V/24V Selectable
- Output DC9V and 12V
- 17600mah lithium battery
- Press 2-3 seconds to turn on UPS
- Suitable for small DC communication equipment, network peripherals

Product Instructions

- The UPS automatically begin charging after the power is plugged in
- Manually control output switch
- Overload & short-circuit protection
- Over-charge and over-discharge protection
- Multi-functional LCD screen
- Maximum capacity: 60W
- Application:router, modem,wireless phone,CCTV.,etc.

Warm prompt

For getting more fun and the best possible performance,please read carefully the user manual before you use this product.

Please charge the UPS once every 3 months if it is not used for a long time.

It is normal that the temperature is a bit high during charging.

Please keep the UPS clean and dry, do not wash it with chemistry depurative.

Please protect environment,do not abandon.



NCTS-NU60WP (9V OUTPUT & 12V)

MINI UPS POE PORT 15V/24V SELECTABLE

Technical Specifications

Model: NCTS-NU60WP

GTIN 6295151550441

| Model | NCTS-NU60WP | |
|----------------------------|-----------------------------|-------------------|
| Rated working voltage | 100-240Vac/50-60Hz | |
| Output power | 60W | |
| Output | Each DC interface | POE interface |
| Output voltage(selectable) | 9V/12Vdc | 15V/24Vdc |
| Output polarity | --C+ | +4,5pins -7,8pins |
| Output voltage & current | 12V 3A, 12V 1.5A, 9V 1.8A | 15V 1A, 24V 1A |
| QTY. & capacity of battery | Lithium battery 2200mA*8PCS | |
| Unit dimension(mm) | 169x210x51mm | |
| Net weight(kg) | 0.97kg | |
| Storage temperature | -15°C~45°C | |
| Operating temperature | 0°C~40°C | |

* Product specifications are subject to change without notice.

Support 8+ cctv camera & DVR

